

# Material Safety Data Sheet



Superior Solutions

Zep, Inc.  
1310 Seaboard Industrial Blvd.  
Atlanta, GA 30318  
1-877-I-BUY-ZEP (428-9937)  
www.zep.com

## Section 1. Chemical Product and Company Identification

**Product name** ZEPRIDE - E  
**Product use** Cleaner. Degreaser  
**Product code** 0410  
**Date of issue** 08/18/09 **Supersedes** 06/21/05

## Emergency Telephone Numbers

### For MSDS Information:

Compliance Services 1-877-I-BUY-ZEP (428-9937)

### For Medical Emergency

(877) 541-2016 Toll Free - All Calls Recorded

### For Transportation Emergency

CHEMTREC: (800) 424-9300 - All Calls Recorded

In the District of Columbia (202) 483-7616

### Prepared By

Compliance Services  
1420 Seaboard Industrial Blvd.  
Atlanta, GA 30318

391



MIDLAND TOOL AND SUPPLY  
12771 CAPITAL ST  
OAK PARK MI 48237-3113

Printing date: 08/25/10

## Section 2. Hazards Identification

### Emergency overview

#### DANGER !

CAUSES EYE BURNS. Liquid, spray or mist may produce tissue damage, particularly to mucous membranes of eyes, mouth and respiratory tract. CAUSES SKIN IRRITATION. HARMFUL IF ABSORBED THROUGH SKIN. HARMFUL IF SWALLOWED.

\*Hazard Determination System (HDS): Health, Flammability, Reactivity

3 0 0

**NOTE:** MSDS data pertains to the product as delivered in the original shipping container(s). Risk of adverse effects are lessened by following all prescribed safety precautions, including the use of proper personal protective equipment.

### Acute Effects

#### Routes of Entry

Dermal contact. Eye contact. Inhalation.

#### Eyes

Causes eye burns. Eye exposure may cause severe and permanent eye injury (blindness).

#### Skin

Causes skin irritation. May be harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, or reddening.

#### Inhalation

Over-exposure by inhalation may cause respiratory irritation. Inhalation of the spray or mist may produce severe irritation of respiratory tract, characterized by coughing, choking or shortness of breath. Can cause central nervous system (CNS) depression.

#### Ingestion

Harmful if swallowed. May cause burns to mouth, throat and stomach.

### Chronic effects

Overexposure of this product by inhalation or absorption can produce central nervous system depression resulting in headache, nausea and/or dizziness. Repeated or prolonged contact with spray or mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection. Contains material which may cause damage to the following organs: blood, kidneys, liver, upper respiratory tract, skin, eyes, central nervous system (CNS).

### Carcinogenicity

No known significant effects or critical hazards.

### Product/ingredient name

Not available.

Additional Information: See Toxicological Information (Section 11)

## Section 3. Composition/Information on Ingredients

Name of Hazardous Ingredients	CAS number	% by Weight
ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve	111-76-2	10 - 20
SODIUM XYLENE SULFONATE	1300-72-7	1 - 10
SODIUM METASILICATE; silicic acid (H <sub>2</sub> -Si-O <sub>3</sub> ) disodium salt; water glass	6834-92-0	<5
SODIUM TRIPOLYPHOSPHATE	7758-29-4	<5
ALCOHOLS, C9-11, ETHOXYLATED; linear primary alcohol ethoxylate	68439-46-3	<5

**Section 4. First Aid Measures**

- Eye Contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention immediately.
- Skin Contact** Flush affected skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Wash clothing before reuse. Get medical attention if irritation develops.
- Inhalation** Move exposed person to fresh air. If irritation persists, get medical attention.
- Ingestion** Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. If affected person is conscious, give plenty of water to drink. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Section 5. Fire Fighting Measures**

National Fire Protection Association (U.S.A.)



- Flash Point** None.
- Flammable Limits** Not available.
- Flammability** Non-combustible.
- Fire hazard** In a fire or if heated, a pressure increase will occur and the container may burst.
- Fire-Fighting Procedures** Use an extinguishing agent suitable for the surrounding fire.

**Section 6. Accidental Release Measures**

- Spill Clean up** Put on appropriate personal protective equipment (see section 8). Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

**Section 7. Handling and Storage**

- Handling** Put on appropriate personal protective equipment (see section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Wash thoroughly after handling. Do not reuse container. Observe label precautions.
- Storage** Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Protect from freezing. Do not store in unlabeled containers. Keep out of the reach of children.

**Section 8. Exposure Controls/Personal Protection****Product name**

ETHYLENE GLYCOL MONOBUTYL ETHER; 2-butoxyethanol; butyl cellosolve

SODIUM METASILICATE; silicic acid (H<sub>2</sub>-Si-O<sub>3</sub>) disodium salt; water glass  
SODIUM TRIPOLYPHOSPHATE**Exposure limits****ACGIH TLV (United States). Skin**

TWA: 20 ppm 8 hour(s). Form:

**OSHA PEL (United States). Skin**

TWA: 50 ppm 8 hour(s). Form:

**Supplier Suggested (United States).**CEIL: 2 mg/m<sup>3</sup> Form:**ACGIH TLV / OSHA PEL (United States).**TWA: 5 mg/m<sup>3</sup> 8 hour(s).**Personal Protective Equipment (PPE)**

- Eyes** Splash goggles.
- Body** Wear appropriate protective clothing to prevent skin contact. Recommended: Neoprene gloves. Rubber gloves. Nitrile gloves.
- Respiratory** Use with adequate ventilation. Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Wear appropriate respirator when ventilation is inadequate.

**Section 9. Physical and Chemical Properties**

- Physical State** Liquid. [Thin liquid]
- pH** 12.5 to 13.5
- Boiling Point** 104.44°C (220°F)
- Specific Gravity** 1.03
- Solubility** Soluble in the following materials: cold water and hot water.
- Color** Blue.
- Odor** Mild. Solvent-like.
- Vapor Pressure** 0.0016 kPa (0.012 mm Hg)
- Vapor Density** Not determined.
- Evaporation Rate** 1 (Water = 1)
- VOC (Consumer)** 104.7 (g/l). 0.87 lbs/gal 10.18%



**Section 10. Stability and Reactivity**

**Stability and Reactivity** The product is stable.

**Incompatibility** Reactive or incompatible with the following materials: oxidizing materials and acids.

**Hazardous Polymerization** Will not occur.

**Hazardous Decomposition Products** carbon oxides (CO, CO<sub>2</sub>)

**Section 11. Toxicological Information****Acute Toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
Ethylene Glycol Monobutyl Ether	LD50 Dermal	Guinea pig	>2000 mg/kg	-
	LD50 Oral	Guinea pig	1200 mg/kg	-
	LC50 Inhalation Vapor	Guinea pig	>633 ppm	1 hours
Sodium Metasilicate	LD50 Oral	Rat	1153 mg/kg	-
	LD50 Oral	Mouse	770 mg/kg	-
Sodium Tripolyphosphate	LD50 Dermal	Rabbit	>7940 mg/kg	-
	LD50 Oral	Rat	5400 mg/kg	-
Ethoxylated Alcohols	LD50 Dermal	Rabbit	>2000 mg/kg	-
	LD50 Oral	Rat	1400 mg/kg	-

**Section 12. Ecological Information****Aquatic Ecotoxicity**

Not available.

**Section 13. Disposal Considerations****Waste Information**

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Consult your local or regional authorities for additional information.

**Waste Stream** Code: D002  
Classification: - [Hazardous waste.]  
Origin: - [RCRA waste.]

**Section 14. Transport Information**

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label
DOT Classification	Not regulated.	Not applicable.	-	-	

**NOTE:** DOT classification applies to most package sizes. For specific container size classifications or for size exceptions, refer to the Bill of Lading with your shipment.

PG\* : Packing group

**Section 15. Regulatory Information****U.S. Federal Regulations**

SARA 313 toxic chemical notification and release reporting:

**Product name**

Ethylene Glycol Monobutyl Ether

**Clean Water Act (CWA) 307:** No products were found.

**Clean Water Act (CWA) 311:** No products were found.

**Clean Air Act (CAA) 112 regulated toxic substances:** No products were found.

All Components of this product are listed or exempt from listing on TSCA Inventory.

**State Regulations**

**California Prop 65** No products were found.

**Section 16. Other Information**

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.*

*Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*

*\*NOTE: Hazard Determination System (HDS) ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although these ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HDS ratings are to be used with a fully implemented program to relay the meanings of this scale.*